

Safety Data Sheet

HF 411M ALL COLORS

Safety Data Sheet dated 1/7/2020, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier
Mixture identification:
Trade name: HF 411M ALL COLORS
Trade code: 46650
Product colour: ALL COLORS
- 1.2. Relevant identified uses of the substance or mixture and uses advised against
Recommended Use: Polyolefinic based compound for production of cables and profiles
- 1.3. Details of the supplier of the safety data sheet
Company:
FAINPLAST Srl - Zona Ind.Campolungo II fase - 63100 Ascoli Piceno - ITALY
FAINPLAST srl Tel +39 0736 403605 Fax +39 0736 403807
Monday to Friday (from 09:00 to 12:00 and 15:00 to 18:00)
Competent person responsible for the safety data sheet:
msds@fainplast.com
- 1.4. Emergency telephone number
FAINPLAST srl Tel +39 0736 403605 Fax +39 0736 403807
Monday to Friday (from 09:00 to 12:00 and 15:00 to 18:00)

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture
EC regulation criteria 1272/2008 (CLP):
The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).
Adverse physicochemical, human health and environmental effects:
No other hazards
- 2.2. Label elementsymers and those containing elastomers, even if classified as hazardous according to the criteria of this annex, do not require a label.
The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).
Hazard pictograms:
None
Hazard statements:
None
Precautionary statements:
None
Special Provisions:
None
Special provisions according to Annex XVII of REACH and subsequent amendments:
None
- 2.3. Other hazards
vPvB Substances: None - PBT Substances: None
Other Hazards:
No other hazards

SECTION 3: Composition/information on ingredients

- 3.1. Substances
N.A.
- 3.2. Mixtures
Hazardous components within the meaning of the CLP regulation and related classification:

Safety Data Sheet

HF 411M ALL COLORS

Qty	Name	Ident. Number	Classification
>= 50% - < 60%	Aluminum hydroxide	CAS: 21645-51-2 EC: 244-492-7	Substance with a Union workplace exposure limit.
>= 5% - < 7%	Calcium Carbonate (Limestone)	CAS: 1317-65-3 EC: 215-279-6	Substance with a Union workplace exposure limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

Safety Data Sheet

HF 411M ALL COLORS

- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
See also section 8 for recommended protective equipment.
Advice on general occupational hygiene:
Do not eat or drink while working.
- 7.2. Conditions for safe storage, including any incompatibilities
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Adequately ventilated premises.
- 7.3. Specific end use(s)
None in particular

SECTION 8: Exposure controls/personal protection (All substances are incorporated in the polymer matrix)

- 8.1. Control parameters
Aluminum hydroxide - CAS: 21645-51-2
ACGIH - TWA: 1 mg/m³
Calcium Carbonate (Limestone) - CAS: 1317-65-3
TLV TWA - 5 mg/m³ resp - 15 mg/m³ total
DNEL Exposure Limit Values
Aluminum hydroxide - CAS: 21645-51-2
Worker Professional: 3 03 - Exposure: Human Inhalation - Frequency: Long Term, local effects
Consumer: 6.85 04 - Exposure: Human Oral - Frequency: Long Term, systemic effects
PNEC Exposure Limit Values
N.A.
- 8.2. Exposure controls
Eye protection:
Not needed for normal use. Anyway, operate according good working practices.
Protection for skin:
No special precaution must be adopted for normal use.
Protection for hands:
Not needed for normal use.
Respiratory protection:
Not needed for normal use.
Thermal Hazards:
None
Environmental exposure controls:
None
Appropriate engineering controls:
None

SECTION 9: Physical and chemical properties

- 9.1. Information on basic physical and chemical properties
- | | |
|--|-------------------------------------|
| Appearance and colour: | Cilyndrical granuls diameter 3÷6 mm |
| Odour: | Week or none |
| Odour threshold: | N.R. |
| pH: | N.A. |
| Melting point / freezing point: | 90°÷200°C |
| Initial boiling point and boiling range: | N.A. |

Safety Data Sheet

HF 411M ALL COLORS

Solid/gas flammability:	Above 300°C decomposition with possible emission of fumes
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	N.A.
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Density :	1,0÷1,5 gr/cc
Solubility in water:	Insoluble
Solubility in oil:	N.D.
Partition coefficient (n-octanol/water):	N.A.
Auto-ignition temperature:	>350°C
Decomposition temperature:	> 200°C
Viscosity:	N.R.
Explosive properties:	N.A.
Oxidizing properties:	N.A.

9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.D.
Conductivity:	N.D.
Substance Groups relevant properties	N.A.

* legend section 9:

- NA: The data or feature does not apply to the specific product
- ND: The data or feature, although important to characterize the product, is not available.
- NR: the data or characteristic is not important in evaluating the hazardous characteristic of the substance or preparation.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

When exposed to combustion or thermal or oxidative degradation, develops a complex mixture of airborne solid and gas, including acetic acid, vinyl acetate, ammonia, carbon monoxide and flammable hydrocarbons

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

Aluminum hydroxide - CAS: 21645-51-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 2.3 mg/l - Duration: 4h

Calcium Carbonate (Limestone) - CAS: 1317-65-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be

46650/1

Page n. 4 of 7

Safety Data Sheet

HF 411M ALL COLORS

considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Aluminum hydroxide - CAS: 21645-51-2

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 10000 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 10000 mg/l - Duration h: 48

Calcium Carbonate (Limestone) - CAS: 1317-65-3

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Fish > 10000 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48

e) Plant toxicity:

Endpoint: EC50 - Species: Algae > 200 mg/l - Duration h: 72

12.2. Persistence and degradability

None

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number

Not classified as dangerous in the meaning of transport regulations.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

N.A.

14.6. Special precautions for user

N.A.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

N.A.

Safety Data Sheet

HF 411M ALL COLORS

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
- Dir. 98/24/EC (Risks related to chemical agents at work)
 - Dir. 2000/39/EC (Occupational exposure limit values)
 - Regulation (EC) n. 1907/2006 (REACH)
 - Regulation (EC) n. 1272/2008 (CLP)
 - Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
 - Regulation (EU) 2015/830
 - Regulation (EU) n. 286/2011 (ATP 2 CLP)
 - Regulation (EU) n. 618/2012 (ATP 3 CLP)
 - Regulation (EU) n. 487/2013 (ATP 4 CLP)
 - Regulation (EU) n. 944/2013 (ATP 5 CLP)
 - Regulation (EU) n. 605/2014 (ATP 6 CLP)
 - Regulation (EU) n. 2015/1221 (ATP 7 CLP)
 - Regulation (EU) n. 2016/918 (ATP 8 CLP)
 - Regulation (EU) n. 2016/1179 (ATP 9 CLP)
 - Regulation (EU) n. 2017/776 (ATP 10 CLP)
 - Regulation (EU) n. 2018/669 (ATP 11 CLP)
 - Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

No restriction.

Restrictions related to the substances contained:

No restriction.

Where applicable, refer to the following regulatory provisions :

- Directive 2012/18/EU (Seveso III)
- Regulation (EC) nr 648/2004 (detergents).
- Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

- ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
- SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- ATE: Acute Toxicity Estimate
- ATEmix: Acute toxicity Estimate (Mixtures)
- CAS: Chemical Abstracts Service (division of the American Chemical Society).

Safety Data Sheet

HF 411M ALL COLORS

CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.